

9 Customers API: How to delete a handle

This is a series of articles dedicated to managing customer objects via Openprovider API.

This is a fourth article in a series in which we are going to cover customer handle deletion. To get more information about our API in general, please use our [documentation portal](#) as your reference.

Deleting a handle

This article shows how to delete a customer. Handle deletion removes an existing customer object and all its records.

NB *The operation will only succeed if no domains (or other objects) are linked to this customer handle.*

The name of the handle is the only parameter that is required to perform this operation.

↓ Use endpoint path below. Base URL is determined by both the target environment and API version.

```
DEL {base\_url}/customers/{handle}
```

REQUEST VALUES

Name	Type	Description
handle	string	Required.

REQUEST EXAMPLE

```
curl -L -X DELETE 'https://api.openprovider.eu/v1beta/customers/TP123456-NL' \  
-H 'Authorization: ,Bearer 811eac2d-*****-06aa469aeb61' \  

```

RESPONSE EXAMPLE

```
{  
  "code": 0,  
  "desc": "",  
  "data": {  
    "success": true  
  }  
}
```

Depending on the outcome, one will either receive code 0 (in case of success) or an error code with an error message.

Revision #4

Created 2026-08-13 10:01:39 UTC by Sarath

Updated 2026-08-20 19:03:41 UTC by Sarath